

3D Laser Interferometer for Spin-Graviton Detection and Polar Anisotropy Measurement (Patent #1)

Comprehensive Academic Treatise, Metrological Calculation, and Prior Art Patent Search Report

Author: Yuri A. Chesnokov • ORCID: 0009-0008-5869-0047 • CERN / Zenodo DOI: 10.5281/zenodo.23427637

EXECUTIVE SUMMARY & GLOBAL NOVELTY: This document establishes world author priority for Invention Patent #1: 'Three-Dimensional Tetrahedral Laser Gravitational Interferometer with Closed Optical Channels for Graviton Polarization and Multiverse Tidal Vector Detection'. Unlike planar (2D) gravitational wave detectors (LIGO, Virgo, KAGRA) which are physically blind to scalar/vector longitudinal components and polar spin polarization, the present 3D tetrahedral geometry (4 nodes, 6 independent optical baselines) resolves the complete 3D metric perturbation tensor h_{ij} and detects direct gravitational drift toward the cosmic Axis of Evil (IC 1101 — Phoenix A).

1. Limitations of Existing 2D Detectors & Fundamental Motivation

Existing ground-based laser interferometers (LIGO Hanford/Livingston, Virgo, KAGRA) employ planar L-shaped Michelson topologies with two orthogonal 4-km arms. Their fundamental physical limitations include:

- **Planar Degeneracy:** A single 2D interferometer measures only a single strain projection $h(t) = 1/2 (h_{xx} - h_{yy})$, leaving longitudinal h_{zz} and cross-polarization components completely unconstrained.
- **Blindness to Polar Drift:** Planar detectors cannot measure static or quasi-static directional gravitational flow (Dark Flow / Multiverse pull) along the cosmological Z-axis.
- **Absence of Vertical Baseline:** Ground-based 2D setups lack vertical sensitivity necessary to decouple local seismic/tidal gradients from global spin-graviton polarization.

2. Technical Solution: Tetrahedral 3D Spatial Geometry (Patent #1)

The Chesnokov 3D Interferometer implements a regular spatial tetrahedron with 4 vertex transceiver stations and 6 closed laser baselines $L_1 \dots L_6$:

- **Orbital Configuration (Space-Based):** 3 satellites positioned in Geostationary Orbit (GEO, radius $R_{GEO} = 42,164$ km, inter-satellite spacing $L = 73,028$ km) forming the equatorial base triangle, coupled with 1 polar satellite at high apogee ($R_{polar} = 80,000$ km) aligned along the northern spin axis (+Z, Draco / IC 1101).
- **Terrestrial Configuration (Deep Shaft Base):** A ground-based equilateral triangle (arms $L = 100$ m – 3 km) coupled with a deep vertical shaft station (-Z, depth $H = 100$ m – 3 km) using stabilized invar/vacuum optical conduits and Nd:YAG lasers (1064 nm) with high-finesse Fabry-Pérot cavities (Finesse > 100,000).

3. Mathematical Foundation & 3D Tensor Resolution

The differential phase shift along baseline vector n_k between vertices i and j is rigorously derived as:

$$\Delta \Phi_k(t) = \frac{\omega_0}{c} \int_0^L \frac{1}{2} n_k^i n_k^j h_{ij}(t - t_0 + n_k \cdot x / c) ds + \frac{\omega_0}{c^2} \int_0^L \Phi_{\text{ext}\{\text{grav}\}}(s) ds$$

For 6 simultaneous baseline measurements, the full 3D symmetric strain tensor is reconstructed without directional degeneracy:

$$\mathbf{h}_{3D} = \begin{pmatrix} h_{xx} & h_{xy} & h_{xz} \\ h_{yx} & h_{yy} & h_{yz} \\ h_{zx} & h_{zy} & h_{zz} \end{pmatrix}, \quad \text{ext}\{\text{Polar Strain: } h_{\text{ext}\{\text{polar}\}}\} = h_{zz} - \frac{1}{2}(h_{xx} + h_{yy})$$

4. Industrial & Scientific Applications

- Earthquake & Volcanic Early Warning (6–48 Hours): Deep shaft vertical baselines detect pre-seismic micro-gravitational wave precursor strains ($h \sim 10^{-12}$) caused by deep crust stress reconfiguration hours before acoustic P/S waves.
- Subterranean Gravimetric Tomography: Sub-microgal sensitivity allows 3D density imaging of mineral deposits, aquifers, and subterranean caverns without drilling.
- Multiverse Dark Flow Verification: Continuous tracking of the secular dipole anisotropy vector pointing toward IC 1101 ($l = 178.5^\circ, b = +32^\circ$).

5. Prior Art Patent Search Matrix (World Novelty)

Patent / System	Geometry	Baselines	Polar Z-Axis	Sensitivity h	Status in SGDM
LIGO (US / NSF)	2D Planar (L)	2 Orthogonal	No (Blind)	10^{-21} (AC only)	Prior Art (2D limited)
Virgo / KAGRA	2D Planar (L)	2 Orthogonal	No (Blind)	10^{-21} (AC only)	Prior Art (2D limited)
LISA (ESA / NASA)	2D Triangle	3 Arms (Planar)	No (Ecliptic)	10^{-20} (0.1 mHz)	Prior Art (No vertical)
Chesnokov (Pat. #1)	3D Tetrahedron	6 Independent	YES (Coaxial +Z)	10^{-23} (DC to kHz)	WORLD AUTHOR PRIORITY

6. Patent Claims (Formula of Invention)

1. A three-dimensional gravitational laser interferometer characterized by four spatial transceiver nodes arranged at the vertices of a regular tetrahedron forming six closed optical interferometric baselines, configured to reconstruct the complete six-component metric tensor h_{ij} .
2. The interferometer of claim 1, wherein three nodes are deployed in geostationary equatorial orbit and the fourth node is positioned in high-apogee polar orbit aligned coaxially with the northern cosmic Axis of Evil (+Z).
3. The interferometer of claim 1, configured as a terrestrial installation comprising three surface perimeter stations and one deep-shaft vertical station connected via stabilized optical vacuum conduits for precursor earthquake detection.