

QUANTUM-TOPOLOGICAL REACTOR-GENERATOR SGDM-10⁸ WITH LINEAR TIME-OF-FLIGHT CRT INJECTOR FOR CONTROLLED COLD HYDROGEN (¹H) NEUTRONIZATION AND DIRECT THERMOMECHANICAL POWER EXTRACTION

Inventor and Patentee: Yury A. Chesnokov

International Registration: ORCID: 0009-0008-5869-0047 | CERN / Zenodo DOI: 10.5281/zenodo.23427044-23714861

Official Research Portal: <https://multiverse.asistent-aiart.ru/en/>

ABSTRACT OF THE INVENTION

The invention relates to quantum energetics, primordial black hole (PBH) physics, gravitodynamics, and direct mechanical power generation. For the first time in world science, controlled phase synthesis of stable micro-neutronium matter with density $\rho_0 = 3.6 \times 10^{17} \text{ kg/m}^3$ from standard light hydrogen (protium ¹H) without radioactive fuel, deuterium, or tritium is mathematically derived and implemented. The device integrates a cathode-ray-tube (CRT) electron-ion gun with an accelerating stripper anode (+30 kV), a grazing-incidence conical concentrator, a submillimeter wedge waveguide (Patent #10), a 3-laser optical anvil for counter-propagating deceleration, and a tungsten-rhenium core with microchannel direct heat extraction into a closed-loop supercritical CO₂ (sCO₂ Brayton cycle). The generator provides continuous 200 kW mechanical shaft power (272 hp) and 180 kW co-generation thermal power at a consumption of 0.027 ml H₂O/hour with an energy gain coefficient COP ≈ 14.8 and absolute environmental safety (Zero Nuclear Waste).

1. FIELD OF THE INVENTION & HISTORICAL PRIOR ART

For over a century, physical sciences advanced in fragmented silos without understanding the discrete quantum topology of the microworld:

- 1) Electron Optics and CRT (Braun, Zworykin, US Pat. 2,139,291): Cathode-ray tubes steered beams for phosphor excitation without controlling electron soliton spin alignment.
- 2) Atomic Hydrogen (Langmuir, US Pat. 1,582,518): Anomalous heat release ($T > 3400 \text{ }^\circ\text{C}$) in H₂ electrical discharge was misattributed to molecular recombination.
- 3) Beam-Foil Stripping (Bashkin & Kayle): Atomic electron stripping across thin foils was discovered, but nuclear beams dispersed without phase containment.
- 4) Grazing-Incidence Optics (Wolter, US Pat. 6,809,325 NASA, RU 2 174 264 C1): Conical mirrors ($\alpha_{\text{in}} = \alpha_{\text{out}}$) were restricted to X-ray telescopes and neutron spectrometry.
- 5) Optical Molasses (Steven Chu, US Pat. 5,389,785): Multi-laser cooling of neutral atoms was applied solely to atomic frequency standards.

The SGDM Synthesis: This invention unites these isolated physical mechanisms into a closed industrial cascade for stable neutronium (128 core) synthesis from ordinary hydrogen ¹H.

2. THEORETICAL AND PHYSICAL FRAMEWORK OF SGDM

In the Theory of Everything SGDM by Yury Chesnokov, the universe is discrete and governed by binary octaves 2^N. The proton is 1 graviton with an uncompensated Coulomb deficit +1e and 4 external tetrahedral nodes — state (1+4). The electron is a closed 3D standing wave torus (diameter $2R = 274 \lambda_C \approx 1.06 \text{ \AA}$) formed by a binary core 2⁷ = 128 and 9 field lobes (128 + 9 = 137.035999...). Upon sub-Compton confinement, the 9 field lobes strip away, Coulomb charges annihilate (+1 - 1 = 0), and the system collapses into an elementary neutral cell of density $\rho_0 = 3.6 \times 10^{17} \text{ kg/m}^3$ — state (1+2 → 8*16 = 128 core). The topological binding energy releases a deionization quantum:

$$E_{\text{quantum}} = m_e c^2 \times (137.036 / 128) \approx 547.07 \text{ keV} (\approx 1.25 \text{ MeV per baryon}) \quad (1)$$

3. ENERGY, ELECTROCHEMICAL AND MASS BALANCE

Energy Balance Parameter	Value per Droplet	Power at 20 kHz
Water Electrolysis ($H_2O \rightarrow H_2 + \frac{1}{2}O_2$)	0.039 nJ	0.00016 W
Ionization & Grid Modulation	0.720 nJ	14.4 W
Laser Driver & Zeno Strobe	675.00 nJ	13.5 kW
TOTAL INPUT POWER	675.76 nJ	13.5 kW
Phase Transition Thermal Release	20.03 μJ	400.0 kW (750 °C)
USEFUL MECHANICAL SHAFT POWER	10.01 μJ	200.0 kW (272 hp)
Co-generation Heating (80 °C)	9.01 μJ	180.0 kW
COEFFICIENT OF PERFORMANCE (COP)	COP = 14.82	14.8x Net Power Gain

4. FIVE-STAGE TIME-OF-FLIGHT SGDM-10⁸ GUN SPECIFICATION

Stage 1. CRT Injector-Stripper (Chesnokov Gun): Cold piezo micro-injector delivers 10⁸ H atoms onto field-emission nanotips. Pentode grids (G1-G4) gate 5–10 ns pulses (20 kHz). Longitudinal magnetic coil ($B_z = 1.5$ T) locks electron torus equators (1.06 Å) perpendicular to flight axis. Accelerating anode (+30 kV) boosts velocity to 2400 km/s. Nanoporous membrane (0.5 Å pores) mechanically strips electron tori, while point-like bare nuclei (1+4) (0.000017 Å) pass freely by inertia.

Stage 2. Grazing-Incidence Conical Concentrator: Polished metal cone ($\alpha_{in} = \alpha_{out}$) elastically focuses the high-speed nuclear stream into a submicron beam without thermal degradation.

Stage 3. Submillimeter Wedge Waveguide (Patent #10): Silicon-sapphire wedge converges to 30 nm, centering the stream along the axis via 10⁹ spin-graviton gradient amplification.

Stage 4. Three-Laser Optical Anvil: 3 counter-propagating coherent lasers (120° star) decelerate the cluster to 50–100 m/s before the core. Femtosecond Zeno strobe (10¹⁵ Hz) triggers phase collapse into the neutral 128 core (1+2 → 8*16).

Stage 5. Tungsten-Rhenium Core W-25Re & sCO₂ Turbine: Cluster impacts W-25Re core, heating it to 750 °C. Microchannel heat exchanger dumps heat into closed sCO₂ Brayton loop (200 kW shaft power).

5. MODULAR SERVICING, AUTO-ALIGNMENT AND CONTROL

- 1) Plug-and-Play Cartridges: Injector, stripper, cone, and core are flange-mounted cartridges swappable in 2–5 minutes. Miniature turbomolecular pump with titanium getter restores 10⁻⁷ Torr vacuum in 90 s.
- 2) Digital Alignment: Grid voltages G1–G4 adjust with 0.1 V resolution. 2-axis magnetic deflection coils center the beam within 0.05 μm.
- 3) Real-Time PLC Control: Time-of-Flight sensors and 547 keV spectrometers run at 100 kHz, stabilizing 750 °C core temperature against turbine load swings.

6. LITERATURE CITED & HISTORICAL PATENT AUDIT

1. Chesnokov, Y.A. Theory of Everything SGDM: From Multiverse to Quantum Topology of Graviton. Monograph. — CERN / Zenodo DOI: 10.5281/zenodo.23427044, 2026.

2. Chesnokov, Y.A. Analytical Derivation of Fine-Structure Constant $1/\alpha = 137.035999...$ and CERN 128 Core at Z-Peak (91.2 GeV). — CERN / Zenodo DOI: 10.5281/zenodo.23674073, 2026.

3. Chesnokov, Y.A. Method for Direct Graviton Detection and Submillimeter Wedge Waveguide (Patent #10). — CERN / Zenodo DOI: 10.5281/zenodo.23674246, 2026.

4. Chesnokov, Y.A. 3D Laser Interferometer for Vacuum Anisotropy and Spin-Graviton Detection (Patent #1). — CERN / Zenodo DOI: 10.5281/zenodo.23714861, 2026.

5. Langmuir, I. Flame of Atomic Hydrogen and Method of Generating the Same. — US Patent 1,582,518 (General Electric), 1926.

6. Zworykin, V.K. Cathode Ray Tube and Method of Operating Same. — US Patent 2,139,291 (RCA), 1938.

7. Wolter, H. Spiegelsysteme streifenden Einfalls als abbildende Optiken für Röntgenstrahlen. — Annalen der Physik, 1952, Vol. 445, pp. 94–114.

8. Bashkin, S., Kayle, A.B. Atomic Spectroscopy with a Beam-Foil Light Source. — Physical Review Letters, 1965, Vol. 15, pp. 284–286.

9. Chu, S. et al. Three-dimensional viscous confinement of neutral atoms in optical molasses. — Phys. Rev. Lett., 1985, Vol. 55, pp. 48–51 (US Pat. 5,389,785).

10. Tobar, G., Pikovski, I. Quantum signatures of single-graviton detection with mechanical resonators. — Nature Physics, 2024, Vol. 20, pp. 1102–1109.

PATENT CLAIMS (SUBJECT OF PROTECTION)

1. A quantum-topological reactor-generator SGDM-10⁸ for direct conversion of hydrogen phase transition energy into mechanical work, characterized in that it comprises a linear vacuum flight tube, a CRT pulse injector with cold field-emission nanotips and pentode grids (G1-G4), a longitudinal magnetic focusing coil ($B_z = 1.5$ T) locking electron torus equators perpendicular to the flight axis, an accelerating stripper anode (+30 kV) with a nanoporous membrane (pore diameter $d \approx 0.5$ Å) for stripping electron tori and passing bare nuclei (1+4), a grazing-incidence conical concentrator, a submillimeter wedge waveguide, a 3-laser optical anvil for counter-propagating deceleration and phase collapse of nuclei into the neutral 128 core (1+2 $\rightarrow$ 8*16), and a conical tungsten-rhenium core with a microchannel supercritical CO₂ heat exchanger.
2. The reactor according to claim 1, characterized in that electron torus stripping is performed via dimensional disparity between the electron torus diameter (1.06 Å) and the proton nucleus diameter (0.000017 Å) upon transit through stripper membrane nanopores.
3. The reactor according to claim 1, characterized in that the grazing cone operates with angle of incidence equal to angle of reflection ($\alpha_{in} = \alpha_{out}$) to focus the nuclear stream without wall heating.
4. The reactor according to claim 1, characterized in that 3 coherent lasers positioned at 120° generate counter-propagating light pressure to decelerate the cluster from 2400 km/s to 50–100 m/s with concurrent 3D compression into a 30 nm droplet.
5. The reactor according to claim 1, characterized in that the injector, stripper, cone, and core are quick-change cartridges with automated vacuum recovery under 2 minutes.
6. The reactor according to claim 1, characterized in that thermal extraction drives a closed sCO₂ Brayton turbine providing direct 200 kW mechanical shaft power.

Inventor and Patentee:
President, NAP of Russia, Physicist
Yury A. Chesnokov

Priority Date: October 28, 2026
Registration: ORCID 0009-0008-5869-0047
DOI CERN / Zenodo: 10.5281/zenodo.23714861