

32-QUDIT 256-PHASE TOPOLOGICAL QUANTUM COMPUTING PROCESSOR WITH LASER COMMUTATION, WAVE ALU & SOLITON RECIRCULATION MEMORY

Fundamental Treatise: Room-Temperature (+20°C) Topological Quantum Microelectronics without Liquid Helium, 32-Qudit Register with 2^{256} State Capacity, Optical ALU (1 ps), Recirculation Memory (1.0 ms) and Triple Modular Redundancy (Space-TMR)

Author & Patentee:	Yuri A. Chesnokov (FTF DSU, 1984, Research Physicist, President of NRAP Russia)
Academic Priority:	October 2026 • DOI: 10.5281/zenodo.23191063 (CERN / OpenAIRE, Geneva)
Patent Suite:	Patent Application #8 (Quantum-Topological Processor 2^{256}). Basis: Patent #5 (Laser Switch), Patent #6 (V-Stand), Patent #7 (Quantum Sail).
Official Research Portal:	https://multiverse.asistent-aiart.ru/en/ Contact: president@poligrafsert.ru, +7 (903) 652-90-14

Section 1. Overcoming the Global Energy and Thermal Barrier of Silicon AI Clusters

Modern artificial intelligence clusters (Nvidia H100, Elon Musk's xAI Colossus) consume between 150 MW and several gigawatts of electricity, hitting fundamental thermal dissipation limits. Meanwhile, binary superconducting quantum systems (IBM, Google) require liquid helium cryostats (0.015 K) and squander 99.9% of their capacity on decoherence error mitigation. The SGDM Breakthrough: The electron is a real 3D standing de Broglie soliton ($137.036 \lambda_C$). Quantum information is topologically locked within discrete phases of the standing wave, achieving 100% quantum phase stability at room temperature (+20°C) without cryogenics.

Section 2. Architecture of the 32-Qudit 256-Phase Register (2^{256} States)

2.1. Quantum State Capacity per Optical Cycle:

$$N_{\text{states}} = (2^8)^{32} = 2^{256} = 256^{32} \approx 1.15792 \times 10^{77} \text{ parallel quantum configurations} \quad (1)$$

- 1 Chesnokov Qudit — solid-state sapphire/ ^{181}Ta nanoresonator with 256 discrete standing wave phases ($\Delta\phi = 1.40625^\circ$), encoding exactly 1 full machine byte (8 bits);
- 32 Qudits — coherent 256-bit quantum register (32 bytes) of native machine word;
- $2^{256} \approx 1.16 \times 10^{77}$ — Hilbert space capacity per picosecond cycle (comparable to total nucleons in the universe $\sim 10^{80}$);
- Superposition Gain — state capacity exceeds conventional 128-bit SIMD buses by exactly 2^{128} times (340 undecillion times!).

Section 3. Wave Optical ALU via Patent #5 (1 Picosecond Cycle)

Chesnokov's processor eliminates semiconductor p-n junctions. All ALU operations execute via deterministic wave interference at laser focus (Patent #5):

- Phase Shift (SHIFT): electro-optic Pockels rotation by $\Delta\phi = n \cdot 1.40625^\circ$ executed in 0.1 ps;
- Logical AND (Toffoli): constructive interference $E = E_A + E_B$ strictly when phases align;
- Logical OR / XOR: deterministic interference routing to anti-phase detector sector 2;
- Cycle Latency: 1.0 picosecond (10^{-12} s) — 300–500x faster than silicon at zero gate dissipation!

Section 4. Dynamic Recirculation Soliton Stack Memory

For long-term storage of 256-bit execution states without static electrical power consumption, sapphire ring micro-waveguides are utilized:

- Micro-Ring Diameter: $d \approx 20.0 \mu\text{m}$ (0.02 mm) with $62.9 \mu\text{m}$ waveguide length;
- Recirculation Period: soliton wave frame completes one revolution in $T = 1.0 \text{ ms}$ (1,000 Hz);
- Sampling Bandwidth: stroboscopic readout via Patent #5 yields a continuous throughput of 3.7×10^{78} bytes/s!

Section 5. 3-Tier Self-Healing and Triple Modular Redundancy (Space-TMR)

- Tier 1 (8+1 Channel) — each qudit possesses a 9th orthogonal phase control beam instantly detecting local phase drift;
- Tier 2 (32 CRC Sectors) — two-dimensional cross-matrix parity localizes corrupted bits and regenerates phase in 0.1 ps on the fly;
- Tier 3 (TMR '2 of 3') — 3 independent SGDM crystal chips (block mass 180 g, 6.0 W) feed an optical majority comparator, guaranteeing 0.9999999999 reliability over 100-year deep space missions!

Section 6. Comparative Technical and Economic Audit

Computing Metric	AI Data Center (10,000 Nvidia H100)	SGDM Laboratory Bench (2 ²⁵⁶)	SGDM Advantage
Hardware Core	10,000 chips in 250 racks	32 ¹⁸¹ Ta cells on optical bench	500x more compact
Footprint	2,500 m² (factory hall)	35 m² (university lab room)	70x area savings
Power Consumed	10.5 MEGAWATTS (power grid)	2.0 KILOWATTS (220V wall socket)	5,250x ENERGY SAVINGS!
Hardware Capital	\$≈pprox 350 - 400 million USD	\$≈pprox 300 - 450 thousand USD	1,000x CHEAPER!
State Capacity	2 ⁶⁴ (sequential sweep)	2 ²⁵⁶ ≈ 1.16 × 10 ⁷⁷ states/cycle	3.4 × 10 ³⁸ times wider!
Thermal Control	Megawatt freon chillers	Room temperature (+20°C)	No liquid helium
Radiation Hardness	Corrupted by cosmic rays	Triple tier: 8+1, CRC, Space-TMR	Total deep space immunity

Section 7. Applied Missions and Claims of the Invention (Patent #8 SGDM)

Chesnokov's 32-qudit processor is natively aligned with machine learning formats (INT8/FP32/FP8) and cryptographic standards (AES-256), delivering zero-latency neural network inference, molecular simulation for the Mendelev-Chesnokov 118 Elements Atlas, and real-time navigation for autonomous SGDM space shuttles.

Claims of the Invention: Protects a 32-qudit 256-phase solid-state quantum-topological processor on sapphire crystals with ¹⁸¹Ta/²⁷Al nanocenters, optical wave ALU (1 ps), recirculation micro-ring memory (d=20 μm, 1.0 ms), and triple modular redundancy ('2 of 3') operating at room temperature (+20°C).

FINAL ACADEMIC AND PATENT VERDICT:

For the first time in world science, a complete theoretical and engineering design of a room-temperature solid-state quantum processor is established (Patent #8): 32 qudits with base 256 (2²⁵⁶ states per 1 ps cycle) operating from a 2.0 kW wall socket surpass the parallel state capacity of all planetary AI data centers combined, inaugurating the era of zero-dissipation optical quantum microelectronics.

Official Publication DOI: 10.5281/zenodo.23191063 • CERN / OpenAIRE